

DOMAN™
BUILDING MATERIALS



BuildingWrap™

WEATHER RESISTANT BARRIER AND AIR BARRIER

THE ULTIMATE BARRIER OF DEFENSE. FOR WHATEVER COMES YOUR WAY.

DOMAN BuildingWrap™ exceeds the competition in durability and performance. But DOMAN BuildingWrap also kicks everything up a notch to offer unrivaled tear strength, exceptional holdout, optimized breathability, and six full months of UV protection.





BuildingWrap™

WEATHER RESISTANT BARRIER

HERE'S HOW WE DEFINE HIGH-PERFORMANCE IN THE INDUSTRY.

DOMAN BuildingWrap excels in all the ways that matter most to true construction pros. For starters, it's rugged—with tear strength that's five times greater than the competition. And while it blocks air and water from getting in, it's smart enough to let moisture out of the wall cavity. That means it stands up to the elements with toughness and intelligence other building wraps can't touch. Plus it delivers incredible durability, efficiency, and safety long after the cladding is up.

LEADING FEATURES AND BENEFITS:

- Superior water holdout defends the wall cavity
- Exceptional air blockage increases energy-efficiency
- Optimal breathability decreases risk of mold growth
- Extraordinary tear strength prevents worksite damage
- Surfactant resistance reduces hazards of oils, soaps, and powerwashing
- UV protection stops rays and provides six months exposure time
- Works with most types of cladding
- Made and backed by an industry leader in housewrap solutions and distributed by DOMAN Building Materials

DOMAN BuildingWrap™ is part of a lineup of rugged, versatile, all-conditions products, including flashings, tapes, and accessories. Use it all together to maximize the strength and effectiveness of your building envelope.

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, we make no warranties, express or implied, other than those warranties described in the DOMAN Building Materials Warranty located online at domanbm.com, subject to the limitations and exclusions described therein.

TYPICAL CHARACTERISTICS:

Basis Weight	D5261	3.024 oz/yd ²
Thickness	D1777	12.9 mils .229 mm
Breaking Strength (Grab Tensile)	D5034	67 lbs MD 73 lbs CD
Trapezoidal Tear Resistance	D5733	30 lbs MD 33 lbs CD
Hydrostatic Pressure Resistance	AATCC 127-1995	>500 cm
Moisture Vapor Transmission Rate	E96-95 A	11.7 perms
Ultraviolet Light Exposure Resistance		6 months
Air Penetration Resistance (Gurley Hill Porosity)		>2500 sec/ 100cc
Air Leakage @ 75 pascals		0.0032 L(S.M ²) ⁱ
Water Resistance Test	D779	PASS
Surface Burning Characteristics		
Flame Spread Index	ASTM E84	Class A
Smoke Spread Index	ASTM E84	PASS
NFPA 285		PASS

ROLL SIZES:

3' x 100'	9' x 100'	10' x 95'	10' x 100'
9.5' x 100'			

ⁱ min >170 ng/Pa.s.m²

ⁱ min <0.02 L(S.M²)

DOMAN™
BUILDING MATERIALS

Scan or visit domanbm.com
for more details.

