

Install the system. Get a lifetime limited warranty.* TYPAR® Building Wrap, along with the full TYPAR® Weather Protection System delivers unbeatable coverage.

*Certain limitations and exclusions apply. See the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads for full details.





TYPAR° BUILDINGWRAP

HERE'S HOW WE DEFINE HIGH-PERFORMANCE IN THE INDUSTRY.

TYPAR BuildingWrap excels in all the ways that matter most to true construction pros. For starters, it's rugged—with tear strength that's five times greater than the competition. And while it blocks air and water from getting in, it's smart enough to let moisture out of the wall cavity. That means it stands up to the elements with toughness and intelligence other building wraps can't touch. Plus it delivers incredible durability, efficiency, and safety long after the cladding is up.

LEADING FEATURES AND BENEFITS:

- Superior water holdout defends the wall cavity
- · Exceptional air blockage increases energy-efficiency
- Optimal breathability decreases risk of mold growth
- Extraordinary tear strength prevents worksite damage
- Surfactant resistance reduces hazards of oils, soaps, and powerwashing
- UV protection stops rays and provides six months exposure time
- Works with most types of cladding
- Lifetime limited warranty*

INSTALL THE SYSTEM. GET A LIFETIME LIMITED WARRANTY."

Take your stand on unbeatable—and comprehensive—defense. Our Building Wraps, Flashings, and Construction Tape create the complete TYPAR® Weather Protection System. Install it all together and get covered by the only lifetime limited warranty in the industry.*

*Certain limitations and exclusions apply. See the TYPAR We	eather Protection System
Limited Warranty located online at TYPAR.com/downloads	for full details.

TYPICAL CHARACTERISTICS:			
Basis Weight	D5261	3.024 oz/yd²	
Thickness	D1777	12.9 mils	
Breaking Strength (Grab Tensile)	D5034	67 lbs MD 73 lbs CD	
Trapezoidal Tear Resistance	D5733	30 lbs MD 33 lbs CD	
Hydrostatic Pressure Resistance	AATCC 127-1995	>500 cm	
Moisture Vapor Transmission Rate	E96-95 A	11.7 perms	
Ultraviolet Light Exposure Resistance		6 months	
Air Penetration Resistance (Gurley Hill Porosity)		>2500 sec/ 100 cc	
"Air-Ins" (Air Leakage Test)		0.0032 L(S.M²) @ 75 pascals	
Water Resistance Test	D779	PASS	
Surface Burning Characteristics (ASTM E84)			
Flame Spread Index	Class A		
Smoke Spread Index	PASS		
NFPA 285	PASS		

ROLL SIZES:				
3' x 100'	5' x 100'	4.5' x 200'	9' x 100'	
9.5' x 95'	9' x 150'	9' x 195'	10' x 100'	
10' x 150'	10' x 195'			

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, we make no warranties, express or implied, other than those warranties described in the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads, subject to the limitations and exclusions described therein





